



## SB 2235 Shore Strip II

SB 2235 Shore Strip II is a fast acting paint stripper for use in the removal several layers of latex, oil based, enamel or spray paints from concrete, masonry or metal in a quick and efficient manner. At less than 20% VOC, the SB 2235 easily meets all Federal and OTC VOC standards for Paint Strippers and Graffiti Removers.

It can also be used to remove sealers, waxes, lacquers and other coatings.

### Preparation

Provide protection for pedestrians, vehicles, roofing and foliage. Test all other non-masonry surfaces for negative reactions and provide protection where required. Remove all loose materials from the surface prior to application. Protect all surrounding areas from possible damage due to spillage or dripping during application.

All projects should start with a test application to determine suitability of the material for the chosen project, method of application and dwell time. Do not use in enclosed areas without sufficient mechanical ventilation to keep vapors below dangerous levels.

### Dilution and Coverage

Dilution: Usually not diluted -- test application recommended  
Coverage: 50 to 100 square feet per gallon -- dependent upon surface texture

### Application

Apply SB 2235 undiluted with solvent resistant brushes or rollers. Allow the remover to work for 15 minutes or more and remove with high pressure water. Brush agitation of the material may be helpful. **Caution: do not allow the remover to dry on the surface. Reapplication will be required to correct for dried material.** Neutralization of the surface, after removal, is not required. Adequate respiratory protection is mandatory and ventilation to prevent the buildup of vapors is necessary. Do not smoke, use near fire or flame, or operate equipment that may produce electrically or mechanically induced sparks.

SB 2235 Shore Strip is for use by professional contractors only. Spray application is not recommended. Beware of drift during application and removal of the material. Extremely porous surfaces may require an additional application. Do not reapply until the surface is dry. Do not make the first application to a damp or wet surface. A wet or damp surface will result in either poor performance or a failure to perform situation. Do not allow vapors to enter the structure.

SB 2235 is not recommended for furniture or other sensitive painted or varnished surfaces. SB 2235 will not remove cementitious coatings. If a ghost remains in the surface after two applications contact ShoreBest rep for other possible corrective action.

### Technical Data

Appearance: Viscous Liquid	pH: ~6
Biodegradable: Yes	Rinsing: Complete
Flash Point: >94 degrees C	Solubility: Emulsifiable
Foaming: Low	Stability: Good
Odor: Mild Solvent	VOC: < 20.0%

### Safety

Causes skin irritation. Causes serious eye damage. May damage fertility or the unborn child.



**DANGER**

Refer to product SDS or product label for hazard statements, precautionary statements and safety information

### Warranty

Shore Corporation warrants that this product conforms to the chemical composition described in the Product Label. SHORE CORPORATION EXPRESSLY DISCLAIMS ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Shore Corporation shall not be responsible for any direct or consequential damages sustained as a result of the use of this product. Further, Shore Corporation shall not be liable for personal injuries, property damage or any other damages as a result of the use of this product, the sole responsibility of Shore Corporation under the within WARRANTY being the replacement of any nonconforming product. Acceptance and use of this product absolves Shore Corporation from any other such liability whatsoever and from whatever source. The within WARRANTY may not be modified or extended by Shore Corporation representatives or distributors, neither of which are empowered to make any product representation inconsistent with the terms hereof.

### Contact

Trained representatives are available to assist with project assistance and product recommendations. Call **412/471-3330**.