



SB 2335 Graffiti Resistant Coating

SB 2335 Graffiti Resistant Coating is a water borne self cross-linking polymer, which forms a durable, film forming coating on most surfaces. SB 2335 will create an oleo phobic (oil repelling) shield against the penetration and adhesion of many graffiti materials to concrete, wood and non-polished masonry surfaces. The SB 2335 has been successful in providing an easy solution for the removal of non-catalyzed paints, spray paints, crayon, permanent markers, motor oils and some other forms of graffiti from porous masonry surfaces. While SB 2335 produces a matte or waxy film on the surface, it will still let moisture vapor go back/forth in response to environmental conditions. SB 2335 is not for use on horizontal surfaces subject to pedestrian traffic.

Preparation

Provide protection for all non-masonry surfaces. Although SB 2335 is not based on sacrificial wax, it will alter the appearance to give a waxy look. Only a test application will determine if there will be any change that might not be acceptable. Allow the test area to dry before making a final determination regarding acceptance for your project.

Dilution and Coverage

Dilution: Product not diluted -- test application recommended
Coverage: Approximately 100 to 200 square feet per gallon -- dependent upon substrate and other conditions

Application

Apply undiluted SB 2335 to a clean dry surface by brush, spray or roller making sure that a thorough saturation of the surface is accomplished. On an average surface the application rate will be about 100 to 200 square feet per gallon. Make sure that during the initial application, sufficient material is applied to the surface. If a second application is necessary it must be applied while the first coat is still wet [wet on wet]. While the material dries to the touch in an about an hour, full cure and maximum solvent resistance requires 12 to 24 hours. A second application is not possible, once the product has dried, to make up for deficiencies due to the water repellent nature of the product.

Do not allow SB 2335 to dry on the surface of equipment or any surface that is not to be treated. After the treatment is completed, immediately clean all equipment with water. During application, any surface that accidentally comes in contact with the treatment must immediately be cleaned with water and rags or other appropriate cleaning material.

Apply SB 2335 to a clean dry surface only. Do not apply when surface and ambient temperatures are below 50 degrees F or above 90 degrees F and if rain is expected within 12 hours. Minimum temperatures must be maintained for at least 12 hours after application. This product was designed for adhesion to uncoated masonry, wood, and metal. SB 2335 may work over some decorative coatings but do to the wide variety of types of coatings it is up to the applicator/building owner to determine compatibility to existing coatings.

Technical Data

Appearance: Milky White	pH: 8 to 9
Flash Point: NA	Stability: Good
Odor: Mild	VOC: 1.45 Lbs/Gallon

Safety

May be harmful if swallowed. May be harmful if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure.



WARNING

Refer to product SDS or product label for hazard statements, precautionary statements and safety information

Warranty

Shore Corporation warrants that this product conforms to the chemical composition described in the Product Label. SHORE CORPORATION EXPRESSLY DISCLAIMS ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Shore Corporation shall not be responsible for any direct or consequential damages sustained as a result of the use of this product. Further, Shore Corporation shall not be liable for personal injuries, property damage or any other damages as a result of the use of this product, the sole responsibility of Shore Corporation under the within WARRANTY being the replacement of any nonconforming product. Acceptance and use of this product absolves Shore Corporation from any other such liability whatsoever and from whatever source. The within WARRANTY may not be modified or extended by Shore Corporation representatives or distributors, neither of which are empowered to make any product representation inconsistent with the terms hereof.

Contact

Trained representatives are available to assist with project assistance and product recommendations. Call **412/471-3330**.